

LogiLink_®

19" KVM Console with 17" TFT-LCD Panel

DE/US Keyboard Layout

Art. No.: LC702GE LC702US

The LCD console module features an integrated 17" TFT-LCD panel with ultra-thin keyboard and touchpad in 1U Rack-mountable housing.

Features:

- » A control platform with LCD, keyboard, mouse and a single port KVM switch
- » Grade A 17" TFT LCD with the maximum resolution of 1280 x 1024@60Hz
- » Ultra-thin keyboard and touchpad in a 1U rack-mountable Slideway™ housing; easily to pull out or slide in
- » 1U height, suitable for 19" standard cabinet installation and metal structure
- » Compatible with most KVM switches
- » LCD module rotates up to 120° for a more comfortable viewing angle
- » Front panel with a lock to prevent damages by any accident
- » Easy to use with the On-Screen-Menu (OSD)
- » Support PS/2 and USB
- » When pulling control platform out from cabinet, the power turns on automatically. When pushing it into the cabinet, the power turns off automatically







Specification:

Computer Connection	1	
CPU Port Selection	Front panel buttons/OSD menu	
Console Connector	Keyboard Mouse Video	Disassembled standard 100-key keyboard Standard PS/2 touch pad USB connector on the front 17" SXGA color TFT-LCD
Cable Connector	Keyboard	1 x PS/2 female (purple), 1 x USB female
	Mouse	1 x PS/2 female (green)
	Video	1 x HDB-15 male (blue)







LogiLink_®

19" KVM Console with 17" TFT-LCD Panel

DE/US Keyboard Layout

Art. No.: LC702GE LC702US

	Monitor	17" SXGA Color TFT-LCD
LCD Monitor	Active Area	337.920(H) x 270.336(V)mm
	Pixel H x V	1280 x 3(RGB) x 1024
	Support Color	16.7M colors (RGB 6-bits + Hi-FRC data)
	White Luminance	250cd/m² (center, Typ)@ 60mA
	Contrast	1000:1 (Typ)
	Back Light	LED
	Pixel Pitch	0.264mm (per one triad) x 0.264mm
	LCD MTBF	50,000 hours
	Input Power	DC 12V
Mouse	X/Y Resolution	1000 dots/inch 40 x 40/mm
	Hardware Connector	Standard PS/2
	OS Support	Win95/98/98SE/ME/2000/XP/Vista/NT/7/10 Unix, Linux
	Life Span	1,000,000 times
Keyboard	Keyboard	100 keys
	Compatible IBM/AT	Win95/98/98SE/ME/2000/XP/Vista/NT/7/10 Unix, Linux
	Port	Standard PS/2 and USB
	Life Span	>1,000,000 times
LED	Online	LED Display
LED	Selected	Nixie Tube Display
	Power (AC)	100V~240V
Power	Life Span	MTBF>60,000 hours 25°C
Housing	Metal (Black)	







LogiLink_®

19" KVM Console with 17" TFT-LCD Panel

DE/US Keyboard Layout

Art. No.: LC702GE LC702US

Dimension	407 x 445 x 44mm	
Installation Dimension	400mm ~ 800mm (adjustable)	
Operating Temperature	0°C ~ 50°C	
Storage Temperature	-20°C ~ 60°C	

Art-No.	Keyboard Layout	EAN Code
LC702GE	DE keyboard layout	4052792045253
LC702US	US keyboard layout	4052792045260



Package Contents:

- » 1 x 17" LCD Console
- » 1 x Power Adapter
- » 1 x DP37 Pins Connection Cable
- » 1 x User Manual

Package Informations:

- » Packing Dimension: 407 x 445 x 44mm
- » Packing Weight: 8.4kg » Carton Dimension: mm
- » Carton Q'ty: 1pcs
- » Carton Weight: 14.2kg



